

ISERIES COMPARISON CHART



SUPERIOR PROTECTION

All SKB iSeries Injection Molded MIL-STD Waterproof Utility Cases are molded of ultra high-strength polypropylene copolymer resin, and feature a gasket-sealed, water- and dust- tight, submersible design that is resistant to corrosion and impact damage (MIL-STD-810G). Other standard features include a molded-in hinge, patented "trigger release" TSA-retrofitable latches, comfortable snap-down rubber over-molded cushion grip handles, automatic ambient pressure equalization valve (MIL-STD-648C), and resistance to UV, solvents, corrosion, and fungus.



FEATURES/BENEFITS

- Lighter & 2.8x stronger than the competition
- Many interior options: empty, cubed/layered/custom foam, padded dividers
- Field-replaceable hardware: latches, handles, hinges, wheels
- Easy-open trigger latches with TSA lock options

ISERIES CASES						PELICAN CASES					STORM CASES					PELICAN AIR CASES						
MODEL #	LENGTH	WIDTH	HEIGHT	WEIGHT (LBS)	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH		
3i-0702-1	7.75	2.125	1.25	0.33	N																	
3i-0705-3	7.5	5	3.25	1.13	N	1120	7.29	4.78	3.33	N												
3i-0806-3	8.5	6	3.625	1.63	N	1150	8.29	5.79	3.75	N	iM2050	9.5	7.5	4.25	N							
3i-0907-4	9.5	7.25	4	2.57	N	1200	9.31	7.13	4.12	N	1300	9.17	7	6.12	N	iM2075	9.5	7.5	7.3	N		
3i-0907-6	9.375	7.375	6	2.88	N	1170	10.54	6.04	3.16	N												
3i-1006-3	10.75	6.125	3.25	1.96	N																	
3i-1208-3	12	8	3.375	2.12	N																	
3i-1209-4	12	9	4.5	3	N	1400	11.81	8.87	5.18	N												
3i-1309-6	13.375	9.5	6.5	4.75	N						iM2100	13	9.2	6	N							
3i-1510-4	15	10.5	4.5	4.63	N																	
3i-1510-6	15	10.5	5.875	5.19	N	1450	14.66	10.24	6.12	N	iM2200	15	10.5	6	N							
3i-1510-9	15	10.375	9	6.07	N											1507	15.15	11.38	8.52	N		
3i-1515-6	15	15	6.5	7.17	N																	
3i-1610-5	16	10	5.5	5.23	N	1470	15.7	10.7	3.87	N												
3i-1610-10	16	10	10	7.26	N																	
3i-1706-6	17	6.5	6.5	4.78	N						iM2306	17	6.3	6.2	N							
3i-1711-6	17	11.5	6	5.91	N	1500	16.75	11.18	6.12	N	iM2300	17	11.7	6.2	N	1485	17.75	10.18	6.15	N		
																1557	17.33	13	9.75	N		
3i-1717-10	17	17	10	10.47	N																	
3i-1717-16	17	17	15.75	13.87	N																	
3i-1813-5	18.5	13	4.75	5.8	N	1490	17.75	11.37	4.12	N	iM2370	18.2	12.1	5.2	N							
3i-1813-7	18.5	13	7	7.71	N	1520	18.06	12.89	6.72	N	iM2400	18	13	6.7	N							
																1506	18.7	9.4	7.8	N		

iSERIES COMPARISON CHART



iSERIES CASES						PELICAN CASES					STORM CASES					PELICAN AIR CASES				
MODEL #	LENGTH	WIDTH	HEIGHT	WEIGHT (LBS)	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH	MODEL #	LENGTH	WIDTH	HEIGHT	PH/WH
						1460	18.54	9.92	10.92	N						1465	18.62	9.99	10.93	N
3i-1914N-8	19	14.25	8	8.17	N	1550	18.63	14.18	7.72	N	iM2450	18	13	8.4	N					
3i-1914-8	19	14.375	8	13.19	Y															
3i-2011-7	20.375	11.5	7	11.2	Y	1510	19.75	11	7.6	Y	iM2500	20.5	11.5	7.2	Y	1535	20.39	11.2	7.21	Y
3i-2011-8	20.5	11.5	8	7.97	N											1525	20.5	11.31	6.75	N
3i-2011-10	20.375	11.125	10.625	12.75	Y											1556	21.63	10.76	8.97	Y
3i-2015-7	20.5	15.375	7.375	9.27	N						iM2600	20	14	7.7	N					
3i-2015-10	20.5	15.5	10	14.27	Y	1560	19.92	14.98	9	Y	iM2620	20	14	10	Y					
3i-2213-12	22	13	11.75	16.32	Y															
3i-2215-8	22	15.5	8	16.02	Y															
3i-2217-8	22	17	7.875	11.12	N	1600	21.51	16.54	7.99	N	iM2700	22	17	8	N					
3i-2217-10	21.875	16.875	10.375	17.49	Y	1610	21.78	16.69	10.62	Y	iM2720	22	17	10	Y					
3i-2217-12	22	17	12.5	18.57	Y	1620	21.48	16.42	12.54	Y	iM2750	22	17	12.7	Y	1607	21.1	15.8	11.6	Y
3i-2222-12	22.5	22.25	12.25	21.8	Y						iM2875	22.5	21.1	11.4	Y					
																1555	23	12.75	7.5	N
3i-2317-14	23	17	14	20.8	Y											1637	23.43	17.55	13.25	Y
3i-2418-16	24	18	16	22.2	Y															
																1606	24.54	12.3	10.22	Y
3i-2421-7	24	21	7	18.85	Y															
3i-2424-10	24	24	10	23.59	Y															
3i-2424-14	24	24	14	25.39	Y	1640	23.7	24	13.9	Y										
3i-2615-10	26	15	10	19	Y											1605	26	14	8.38	N
3i-2617-12	26	17.5	11.875	20.89	Y															
3i-2620-13	26	20	13	23.5	Y															
3i-2914-15	29	14	15	20.18	Y											1626	28.14	14.1	11.72	Y
3i-2918-10	29	18	10.75	22.13	Y	1650/1670	28.57	17.52	10.65	Y	iM2950	29	18	10.5	Y					
3i-2918-14	29	18	14	24.2	Y						iM2975	29	18	13.8	Y	1646	32.06	15.87	13.42	Y
3i-2922-10	29	22	10.375	26.81	Y															
3i-2922-16	29	22	16	28.25	Y	1630	27.7	20.98	15.5	Y										
3i-3016-10	30	16	10	17.58	Y	1615	29.59	15.5	9.38	Y						1615	29.59	15.5	9.38	Y
3i-3019-12	30.5	19.5	12	23.59	Y															
3i-3021-18	30	21	18	29.93	Y	1660	28.2	19.66	17.63	Y	iM3075	29.8	20.8	17.8	Y					
3i-3026-15	30.75	26	15.5	31.46	Y	1690	30.13	25.13	15.36	Y										
3i-3424-12	34.5	24.5	12.75	29.94	Y	1730	34	24	12.5	Y										
3i-3613-12	36	13.5	12	20.23	Y															
3i-3614-6	36.5	14.5	6	15.39	Y	1700	35.75	13.5	5.25	Y	iM3100	36.5	14	6	Y					
3i-3913-12	39.375	13.5	12.375	22.23	Y															
3i-4213-12	42.375	13.5	12	22.8	Y	1740	40.98	12.92	12.13	Y										
3i-4214-5	42.5	14.5	5.25	16.46	Y	1720	42	13.5	5.25	Y	iM3200	44	14	6	Y					
3i-4217-7	42.5	17	7.5	20.4	Y											1745	44.01	16.77	7.94	Y
3i-4414-10	44.5	14.5	10	22.89	Y						iM3220	44	14	8.5	Y					
3i-4719-8	47	19	8	24.03	Y															
3i-4909-5	48.75	9	5	12.62	N															
3i-5014-6	50.5	14.5	6	18.73	Y	1750	50.5	13.5	5.25	Y	iM3300	50.5	14	6	Y					
3i-5616-9	56	16	9	28.47	Y	1770	54.58	15.57	8.63	Y	IM3410	54.5	10	6	Y					
3i-6018-8	59.875	18	8	28.59	Y															